

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 January 2001 (25.01.2001)

PCT

(10) International Publication Number
WO 01/05692 A1

(51) International Patent Classification⁷: **B65G 65/23,**
69/16

(21) International Application Number: PCT/NZ00/00126

(22) International Filing Date: 14 July 2000 (14.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
336794 16 July 1999 (16.07.1999) NZ

(71) Applicant (for all designated States except US): **TAYLORS ENGINEERING (BLENHEIM) LIMITED**
[NZ/NZ]; 47 Grove Road, Blenheim (NZ).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TAYLOR, Geofrey, James, Wolfe** [NZ/NZ]; Hammerichs Road, RD3, Blenheim (NZ). **TAYLOR, Wayne, Matthew** [NZ/NZ]; Tyntesfield Road, RD6, Blenheim (NZ).

(74) Agent: **BUCHANAN, Elspeth, Victoria; P.L. Berry & Associates**, P.O. Box 1250, Christchurch (NZ).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS FOR EMPTYING RECEPTACLE



(57) Abstract: Apparatus (2) for emptying the contents of a receptacle (22, 23) in which the receptacle is suspended by a collar (20, 21) surrounding the receptacle from a stationary support frame (3a, 3b) which rests on ground or equivalent supporting surface; the collar is pivoted to the support frame and a moving means such as a pair of space hydraulic rams (18, 19) is mounted between the collar and the support frame; operation of the rams tilts the receptacle in a controlled manner to move the receptacle between a first substantially upright position (L) and a second inclined position (R) in which the contents of the receptacle can be poured out.

205110 98010001

WO 01/05692 A1